



Control



OTR



Winter

# NXRMS1 NXRMS1L

**Winter optimized compound for excellent traction on snow and ice**

- Snow compound for snow and icy roads
- Excellent traction in snow condition
- Light construction for loader only\*\*
- High speed durability



## Application



Loader



Dozer



Grader



Winter

| Size      | TRA   | LISI       | Star rating | TL/TT | Standard rim | Section width | Diameter | Standard pressure | Weight | Tread depth |
|-----------|-------|------------|-------------|-------|--------------|---------------|----------|-------------------|--------|-------------|
|           |       |            |             |       |              | (mm)          | (mm)     | (bar)             | (kg.)  | (mm)        |
| 14.00R25* | E2    | 170E       | ***         | TL    | 10.00/1.5    | 373           | 1.352    | 10,00             | 163    | 23,0        |
| 15.5R25*  | E2/L2 | 160B/176A2 | **          | TL    | 12.00/1.3    | 394           | 1.277    | 6,50              | 131    | 25,0        |
| 16.00R25* | E2    | 174F/177E  | ***         | TL    | 11.25/2.0    | 432           | 1.493    | 7,00              | 214    | 28,0        |
| 17.5R25** | E2/L2 | 167B/182A2 | **          | TL    | 14.00/1.5    | 445           | 1.348    | 6,50              | 169    | 28,0        |
| 20.5R25*  | E2/L2 | 177B/193A2 | **          | TL    | 17.00/2.0    | 521           | 1.490    | 6,50              | 228    | 31,0        |
| 23.5R25** | E2/L2 | 185B/201A2 | **          | TL    | 19.50/2.5    | 597           | 1.617    | 6,50              | 324    | 34,0        |
| 26.5R25*  | E2/L2 | 193B/209A2 | **          | TL    | 22.00/3.0    | 673           | 1.750    | 6,50              | 447    | 37,0        |
| 29.5R25*  | E2/L2 | 200B/216A2 | **          | TL    | 25.00/3.5    | 750           | 1.873    | 6,50              | 580    | 43,5        |

\* NXRMS1

\*\* NXRMS1L